



WBS 1.07 Small Aperture Telescopes Status

John Kovac


CMB-S4 Collaboration Meeting
May 9-13, 2022



SAT Team





L2: John Kovac
Harvard Univ



CAM: Bobby Besuner
(LBNL)

+ technical input from
SAT Working Group
(includes all S4 institutions,
meets weekly)




Bobby



Tim



Joe



Akito



Scott



Abby



Paul



Kirit



Clem



Ben



Akito







Tim

L3 Contributors and Working Group Members: Ken McCracken (SAO), Ed Tong (SAO), Tony Stark (SAO), Fred Matsuda (Kavli IPMU), Keith Thompson (SU), Brad Johnson (UVA), Tomotake Matsumura (Kavli IPMU), Marion Dierickx (HU), Nicholas Galitzki (UCSD), Shaul Hanany (UM), James Cornelison (HU), Tyler St. Germaine (HU), Clara Vergès (HU), Matthew Petroff (HU), David Goldfinger (HU), and no doubt many others who have called in...



SAT Scope

Cryostat System, Optics Tubes, Integration & Test



Telescope Mount, Ground Shield, Calibration Equipment

Integration and Test
(including modules,
readout, DAQ)
before shipping to site




30/40 GHz
85/145 GHz
95/155 GHz
220/270 GHz

SAT Receiver and Cryostat Design Overview




Joe



Akito


3x Receiver Tubes
(each with an optics tube and focal plane)



1 Dilution Refrigerator,
3x PT410s

Cryostat Bus

- SAT design draws directly on design heritage from BICEP3, BICEP Array, and Simons Observatory Small Aperture Telescope Receivers
- Design is maturing this year, driven by prototype test schedule
- Baseline cryostat power: 27 kW



SAT Optics Design

- Baseline **controls science risks** → clean, compact, extremely high throughput
 - builds on **only** proven approach for deep r measurements
- Recent developments:
 - **slightly curved focal surface** ($r = 2.4$ m) dramatically improves performance of two-lens designs
 - **MF optics / pixel layout study** defined baseline coupling for MF1/MF2
 - **initial material measurements** have bounded loss / birefringence in HDPE
- HDPE now baselined for all frequencies; alternatives to be evaluated








Scott



Abby



Paul





SAT Mount Overview



Clem

Flexible Environmental Enclosure

DR Gas Handling System



Interface to SAT Tower
(Pole Site ICD [CMBS4-doc-348](#))

Receiver - Mount
Interface Struts


3 axis balanced
360-boresight

Heritage: BICEP Array Mount Integration, Deployment, Site Interface




BICEP Array Mount
@ UMN (Aug 2020)

BICEP Array Mount
@ Pole (2021)



Mount #2
under fab now



S4 SATs mount
and groundshield
(total 6 planned)

- BART (BICEP Array Replacement Tower) – design adopted, confirmed to meet CMB-S4 baseline reqts.


Ground Shields

Key elements of proven approach to systematics control:


- Cylindrical warm forebaffles
- Reflective outer groundshield

Under double-diffraction criterion, at 50 degrees minimum elevation, geometry study found SAT 3-tube receiver can be shielded with:


- **Forebaffle:** 1.75 m tall, 0.8 m radius
- **Ground Shield:** 5.9 m tall, 12.4 m radius




bicep3 100 Ground T Map Coadded over all Dets





Ben



SAT Calibration Apparatus



- Far-field measurements using a redirecting flat mirror, sources on masts
- Some apparatus also needed for prototype test and I&T validation
- Major effort on standardizing definitions and refining requirements (Kirit/Clara)




Thermal choppers
24" aperture
(precision beams)




Kirit

Broad-spectrum noise sources (polarization, sidelobes)



Spectrometers (bandpass)



SAT current focus:

- **Maturing the baseline design**
 - **Cryostat** advancing toward readiness for prototype build
 - **Optics** component-level prototype measurement and alternatives assessment
 - **Calibration** plan oriented toward validation/acceptance goals
 - **I&T plan** is sufficiently mature for present (thanks to Tim & Akito + Joe, Ben)
 - **Mount and Tower** design mature (mount #2 under construction!)
- **SAT Opportunities**
 - BART mount and tower designs now confirmed to meet CMB-S4 requirements
 - LOI states plan for reuse by CMB-S4; working on how to fold into project plan and AoA
- **SAT Systems Engineering, R&D to build Margin and Mitigate Risk**
 - Power savings – reducing cooling needs per SAT (baseline 27kW)
 - Baseline design: use of inverter compressors (CPA286i) and load reduction could get to ~18 kW
 - Alternative designs: “Big SAT” rather than 3-shooter, possibly < 18 kW
 - Sensitivity increases – aiming for more science per SAT
 - Optics optimizations (thinner window, less scattered forebaffle loading, etc.)
 - Pushing to higher pixel densities, either with more aggressive optics or alternate DRM technologies
 - pSAT (pathfinder SAT) – (single tube 100mK SAT prototype using existing BA cryostat)
 - Proposed avenue for cold optics subsystem testing, designed to retire science performance risk
 - Could be used to explore sensitivity tradeoffs

Summary


- SAT has an experienced team in place
- The SAT Baseline Design has been developed to meet its uniquely challenging measurement requirements
- Risks / hazards and mitigations are guiding our R&D and design effort
- Analyses of alternatives are being used effectively, collapsing design space
→ consider additional **engineering** and **science risks** for alternatives beyond baseline
- The SAT team has a clear path to readiness for CD-1



BACKUP SLIDES

SAT Cryostats Design and Heritage

Cryogenic Bus Assembly is based on BICEP Array Heritage



S4 SAT


Leveraging integration & test experience with arrays of SAT cryostats from multiple Stage 3 projects




BICEP Array SATs

Cold Optics Heritage


BICEP3




Simons Observatory



Silicon AR Example (Michigan/Chicago)



Alumina AR Example (Illinois)




Optics design based on matured approach, but experience shows for every design, prototype testing is essential.

AR coating is a major R&D item. Technology shared with LAT.

Recent SAT L2/L3 Highlights



Management:

- Working with South Pole Sites L2, ensured SAT Tower and related requirements updated in the South Pole Sites - SATs ICD to a level that allowed requirements to be input to Jama:
 - Process documented BART compliance with current state of South Pole Sites and SATs operations plans.
 - Allowed BART structural and civil designs to move forward to fabrication, deemed in compliance with S4 requirements.
- Cost, schedule, and BOEs developed further in P6 and Confluence tools.
- Interface development going on throughout SAT L2, both inside and outside of SATs.



Cryostat Prototyping/Cryostat:

- Met with representatives of three potential dilution refrigerator manufacturers (Bluefors, Janis, Oxford).
 - Progress has been made with vendors focused on packaging options for their gas handling system on the SAT mount.
- Developed pSAT project as an NSF-MRI proposal.
 - The pSAT project would adapt an existing BICEP Array receiver to house CMB-S4 prototype optics, detectors, and readout for lab testing and field deployment to South Pole.



Exclusion Zones (CMB-S4 Requirement) Needed for Cryostat to Mount attachment, and service access



[Joe]

Recent SAT L2/L3 Highlights

Optics Prototyping/Cold Optics:



- Worked with John Ruhl on modelling the SAT Optics system for L1 system design - formulating process for maintaining/documenting sensitivity model for the SAT optics, identifying uncertainties and opportunities for building margin in various configurations (baseline, alternatives).
- Completed design of open cavity resonator for cryogenic materials testing of index and loss, and sent out for manufacturing.
- Continued optical testing of cryogenic baffling material configurations.
- Testing and use of full-scale AR layer lamination press at Harvard.
- Continued development of the Optics Assessment Plan.



[John]

Calibration Equipment:

- Continued analysis of BK beam map data to determine noise scaling with beam map schedule count.
- Worked with South Pole sites group to ensure that roof can accommodate anticipated equipment.
- Worked with South Pole Integration and Commissioning to outline a list of calibration activities and delineate responsibilities.
- Worked to quantify sidelobe map depth with Colin and Rito.
- Working on the initial conceptual design of early calibration equipment systems (cold load, near field beam mapper, etc.).



[Paul]

Recent SAT L2/L3 Highlights

Telescope Mount Assembly:


- Steel part fabrication and assembly welding process ongoing at Colombo Carpenteria for the first SAT-compatible telescope mount assembly (to be deployed on BART tower).
- Gear reducer alternative vendor study completed:
 - Considered cost/benefit of Micron (\$28k cheaper per mount) vs. Parker (original) reducers.
 - Conclusion: Parker is preferred on basis of better service access and stronger intrinsic design with lower risk.



Telescope Ground Shield:

- Coordinated on interface development between South Pole sites and SAT telescope mount, cryostat, and calibration hardware L3s.
- Coordination of planned SAT walkway and roof level activities with South Pole sites laboratory building development effort.
- Developed six conceptual SAT Ground Shield geometric variants, and with input from SAT WG conducted a downselect to two variants:
 - Will further consider a monolithic ground shield design and a vertically-segmented design in more engineering detail.


[Clem/Eric]




Recent SAT L2/L3 Highlights

Integration and Testing Plan Development:

- Developing facility layouts for integration and testing of SAT receivers in LBNL Building 77 (left) and Harvard high bay facility (right).
- Continued interfacing with detector L2 team regarding detector delivery schedule and coordination with SAT integration and testing schedule.



[Joe]



[Ben]